



X-6000 INDUSTRIAL PRINTER

The G-6000 offers the industrial standard 6 inch width to give you high speed performance and greater extension of the printing area. Built-in LCD display, 2 MB flash memory, PS2 interface for your PC keyboard provides the essential structure for Plug and Play stand-alone operation. Perfectly designed metal case resists rough treatment, heat, and dust, and ensures continuous quality operation, even in the most demanding environments. Superior historical control enhances high printing quality, and is perfect for printing of barcode and small alphanumerics. The G-6000 is simple to operate and it is easy for the user to perform adjustments and maintenance.

Specifications

> Printing method	Direct Thermal & Thermal Transfer
> Printing resolution	203 DPI (8 dots/mm)
> Printing Speed	2~6 ips (51~152 mm/s)
> Printing Length	1" ~ 30"(25mm ~ 762mm)
> Printing Width	Max 6.3"(160 mm), Max 6"(152mm) in cutter mode
> Display	Back-lit LCD, 2 line x 6, LED indicators x 3
> Memory	2Mb DRAM, 1Mb Flash ROM
> CPU Type	32 bit RISC Microprocessor
> Media Sensor	Reflective and see-through transmissive
> Compact size	W12.1" x H10.2" x L17.3" (W310 x H260 x L445 mm)
> Ribbon type	Wax, Wax/resin and Resin ; Coating inside
> Ribbon size	OD 2.5 in. (63mm) ID 1 in. (25 mm) Ribbon width - 2", 4", 6" ; Ribbon length - 300M max
> Weight	302lbs (14.5kg)
> Communication interface	Centronics parallel, RS-232 serial
> Maximum label roll diameter	8 in.(203 mm) outside diameter 1.5 in. ~ 3.0 in.(38 mm ~ 76 mm) inside diameter
> Power Source	110/220 VAC ± 10%, 50/60 Hz
> Agency listing	CE, UL, CUL, FCC class A, CCC
> Media	Roll-feed, die-cut, continuous, fan-fold, tags, ticket in thermal paper or plain paper
> Label indexing	Black stripe and gap
> Operation environment	40°F ~ 100°F (4°C ~ 38°C) 10~90% non condensing
> Storage temperature	-40°F ~ 140°F(-4°C ~ 60°C)
> Windows driver	Win98/2000/NT/XP