



R-600 DESKTOP PRINTER

The R-600 inherits the Refine Series' mechanism. Loading capacity accommodates a maximum 360M ribbon roll and 6" OD media supply. Adjustable media guide with centralized alignment fits all variable media from 10mm to 110mm. Easy access via a three-button control panel saves time and requires minimal training allowing the benefits of easy and fast handling. Built-in universal switch power offers 100% flexibility to fit in any local application environment, and it is lightweight, space-saving, and easy to handle. The R-600 maintains high quality printing with 300dpi resolution making it the value-added printer of choice for textile and care labeling applications.

Specifications

| | |
|---------------------------|--|
| > Printing method | Direct Thermal & Thermal Transfer |
| > Printing resolution | 300 dpi (12 dots/mm) |
| > Printing Speed | 2 ~ 4 ips (51~ 102 mm/s) |
| > Printing Length | 0.4" ~ 14" (10mm ~ 355.6mm) |
| > Printing Width | Max 4.0" (101.6 mm) |
| > Memory | 2MB DRAM, 1MB Flash ROM |
| > Ribbon | Wax, Wax/Resin, Resin with inside coating Ribbon width – 2", 4" / Ribbon roll – max OD 2.67" (68 mm) Ribbon length – max 360M wax, 300M Resin) / Core size - ID 1" core (25 mm) |
| > Communication interface | Centronics parallel / RS-232 serial |
| > Power Source | 110/220 VAC ± 10%, 50/60 Hz, internal Universal Power supply |
| > Agency listing | CE, UL, CUL, FCC class A, CCC |
| > Dimensions | W314 x H231 x L218mm, 9.3 lbs (4.2 kgs) |
| > Graphics | PPLA: PCX, BMP, IMG, HEX, GDI PPLB: PCX, Binary raster, GDI |
| > Fonts | Int'l character sets standard 5 alpha-numeric fonts from 0.049"~ 0.23"H (1.25mm~6.0mm) All fonts are expandable up to 24x 24 4 direction 0°~270° rotation Soft fonts are downloadable |
| > Barcodes | Code 39, Extended Code 39, Code 93, Code 128 UCC Code 128(Subset A, B, C) Codabar, Interleave 2 of 5, EAN-8 2&5 add on, EAN-13, EAN-128, UPC, UPC-A, E 2&5 add on, POSTNET, German POST, Matrix 25, Maxicode, PDF-417, Data Matrix |
| > Software | ARGOX PPLA & PPLB Language / Windows Driver (Win98/2000/NT/XP) Label editing software – ArgoBar / Printer Utility |
| > Media | Roll-feed, die-cut, continuous, fan-fold, tags, ticket in thermal paper or plain paper and fabric label with face-in media run way Max width 4.3" (110 mm) / Min width 1" (25 mm) Thickness 0.0025"~. 01" (0.0635mm ~0.254mm) Max roll capacity 6" (152 mm) OD / Core size 1"~1.5" (25mm~37 mm) ID (Core sized 3"ID can be installed by media core adapter) |
| > Optional items | Cutter, Dispenser kit, Real time clock card, ArgoNet print server, USB interface, Asian font card |