

ti
to
ron[®]

LID 571/ISO



- Smallest portable reader
- Store up to 1,600 readings
- Time and date stamp readings
- IRDA interface

LID 571/ISO

The LID-571/ISO Pocket Reader is a low-cost portable reader for applications that do not require maximum read range performance. Typical applications include pet I.D.in veterinary practices and use in inventory applications. The reader will store up to 1600 readings in memory (700 readings with a time and date stamp) and will download them to a PC via an infrared communication channel (maximum range: 1 meter). The LID-571/ISO Pocket Reader will also read FDX-B and Destron 125 Khz transponders, clearly differentiating them from the standard TROVAN UNIQUE™ ID codes.

DIMENSIONS

Width	69.8 mm (2.7 in)
Length	125.4 mm (4.9 in)
Height	24 mm (0.9 in)

WEIGHT

120 gr.

SUPPLY VOLTAGE

9 V battery (not supplied)

SUPPLY CURRENT

Antenna activated	173 mA
Antenna deactivated	26 mA

BATTERY LIFE

Approx. 1 hour (continuous read)

DISPLAY

LCD (2 lines x 16 characters)

MEMORY (Optional)

w/o date/time:	1600 codes
With date/time:	700 codes

INTERFACE (Optional)

Infrared link

TYPICAL READING TIME

24 ms

MATERIAL

ABS UL 94 H

OPERATING TEMPERATURE

0°C - 70°C

READING DISTANCE

ID-100	up to 35 mm (1.38 in)
ID-200	up to 60 mm (2.36 in)
ID-300	up to 45 mm (1.77 in)
ID-400	up to 110 mm (4.33 in)

ACCESSORIES

IR-570 Smart Beam Infrared Link
connects to your PC.(inc. 9 to 25 pin adapter).

LID-570PC Pocket/Belt Clip

PA-570R Rechargeable 9V/160mA Battery

LG-570 9V Battery Charger

PRESENTED BY: